



Decor8
Northern Limited

Silicone Façade Colour Guide

Energy saving masonry coatings



ISO PAINT NORDIC A/S

www.energycoatings.org.uk

colours shown are for indication only

cotswold cream

devon stone

cornish cream

cotswold stone

beige

earthen stone

york stone

silver birch

pebble

cappuchino

soft petal

Isopaint Silicone façade masonry coating

Water repellent, self cleaning, masonry paint.

Isopaint Silicone façade masonry coating is made with pure silicone binders into which micronized marble is mixed to allow moisture to escape.

Product features

- Fully breathable system
- Shuts out water and moisture from the outside
- Will create a dry building and eliminate damp
- Can be mixed to a large colour range
- Available in 9 litre container
- Life expectancy 20 years
- Can be used direct to most masonry substrates



Unit 37, Peel Industrial Estate, Chamberhall Street
Bury, Lancashire BL9 OLU Tel: 0161 763 7007

Technical specifications

- Spreading rate: approx 5 square metres per litre
- Water permeability on painted test pieces:
sd values (m) 0.073 (DIN 52615)
- Capillary water permeability:
W 24 value 0.078KG/square metre (pull of strength)
- Density: 1.45kg per litre

As a result of these features less energy will be required for heating your home, as wet walls transfer heat twice as quickly as dry walls. Without wet walls, you are losing less heat and saving money!

Continuous testing and development

Iso Paint Nordic will continuously test and develop Isonit and the rest of our coating solutions in close cooperation with leading laboratories in Europe.